


# CSX IRT3/IRT4

### 10 CHANNEL INFRARED TRANSMITTERS



## TRANSMITTER FOR INFRARED SPOT AND FLOOD LIGHT

The CSX IRT3 and CSX IRT4 reference infrared radiators transmit up to 10 language channels to conference participants or tour guide groups. Using PPM (Pulse Phase Modulation) technology, always all LED's cover the same area and distance, regardless the number of channels needed in an application. Hence, exact coverage is ensured even if channel needs change.

The CSX IRT3 and 4 can be cascaded almost without limit, due to a signal refresher built in into all transmitters, enabling coverage of very large areas. The transmitters' design eliminates the needs for cooling fans, which also eliminates noise. Clearly visible LED's make the status readable from the distance, enhancing security for onsite technicians.

The CSX IRT3 is the spotlight version with a light angle of +/-17° to cover distances up to 65m, while the CSX IRT4 is designed for near-field use, e.g. in ceilings above the area to be covered. The radiation angle is +/-60° and the working distance up to 35m.

#### **HIGHLIGHTS**

- » Digital Transmission with PPM technology effective audio and radiation quality control – easy to install
- » For CS5 or as standalone system works with all kind of analogue inputs
- » Elegant Design with Status LED clearly displays the status
- » Included signal refresher cascadable to cover large areas

www.akg.com 1



2

» Mounting bar

for wall or ceiling mount

» Two light characteristics - flood and spot light

To work from distance and near field

#### **APPLICATIONS**

- » Conferencing
- » Tour guide
- » Assistive listening

#### KEY SPECIFICATIONS

System description Infrared audio distribution system

Color Matte black

**Power supply** 100-240 volts (1.5A) **System cable coax** 50 ohms (5V TTL)

Wave length 870nM Radiated power 12,5 watts Radiation angle (-6dB) +/- 17° (60°) **Effective distance** 65m (35m) 100 watts **Power consumption** Switch on transient max 2.5 A Height 260mm Width 280mm Depth 70mm Weight 4kg

Included accessories Mounting bar

IEC power cable not included

 Item number CSX IRT3
 6500H00210

 Item number CSX IRT4
 6500H00220



AKG ACOUSTICS GMBH LAXENBURGER STRASSE 254, 1230 VIENNA/AUSTRIA AKG ACOUSTICS, U.S. 8400 BALBOA BOULEVARD, NORTHRIDGE, CA 91329, U.S.A.

© 2015 HARMAN International Industries, Incorporated. All rights reserved. AKG is a trademark of AKG Acoustics GmbH, registered in the United States and/or other countries. Features, specifications and appearance are subject to change without notice.

www.akg.com