

PTZOptics Power Link

Technical Specifications



Connections

- 1 4 x Antenna connectors
- 2 DC 24V Connection
- 3 Gigabit RJ45 port (optional PoE+ output)
- 4 Reset button
- 5 Status LED indicators
- 6 Power Switch
- 7 V-Mount battery plate

In the Box

- Power adapter and cable
- Power Link
- Universal DC24V power supply
- 4 antennas

Transmission

Feature	Specification
Antennas	4x 5 dBi high-gain antennas
Wireless Standard	IEEE 802.11ax/ac/a/b/g/n
Transmission Rate	574 Mbps on 2.4 GHz / 2400 Mbps on 5.8 GHz
Receiver Sensitivity	-98 dBm
Operating Frequencies	2.412-2.472 GHz / 5.180-5.825 GHz
Channel Bandwidth	20/40/80/160 MHz, auto
Encryption	WPA-PSK / WPA2-PSK / WPA/WPA2
Wi-Fi	Wi-Fi 6

Physical

Feature	Specification
Physical Ports	Gigabit RJ45 port (optional PoE+ output), 24V DC port, V-Mount battery plate
Case	Hardened aluminum
PoE+ Port Standard	Up to IEEE 802.3at
Indicators	PWR, PoE+ output status
Switch	On and Off
Mounting	1/4"-20 mounting points
Operating Temperature	-10°C to 50°C
Dimensions with Antennas	7.01" L x 5.22" W x 7.43" H 178.05mm L x 132.59mm W x 188.72mm H
Dimensions without Antennas	5.83" L x 5.22" W x 1.78" H 148.08mm L x 132.59mm W x 45.21mm H
Weight	1.55 lb / 0.70 kg