

## Camera Comparison

All camera models come in either white or grey, and each has a 12X, 20X, and 30X optical zoom variant. In the SKU, the zoom magnification is denoted following the "PT" and the color following the model by either GY or WH. e.g. **PT30X-4K-GY-G3**, **PT30X-4K-WH-G3**

**PTXX-4K-XX-G3:** The Move 4K is capable of 4K at 60fps (1080p at 60fps over SDI). It is our latest and greatest, boasting advanced features like Auto Tracking, Auto Framing, and an enhanced intelligent video production workflow.

**Main Upgrades:** Superior Auto-Tracking and Auto-Framing with presenter select, Built-in tally light, HDMI 2.0, USB 2.0, On-Camera Firmware Updates, Multicast/Unicast

### Move 4K



**PTXX-LINK-4K-XX:** Link 4K fits easily into even the most complex Dante design or workflow. The Link 4K combines broadcast quality with Dante's simple discovery, set up, and management.

**Main Upgrades:** Superior Auto-tracking with presenter select, Built-in tally light, HDMI 2.0, USB 2.0, On-Camera Firmware Updates, Multicast/Unicast.

### Link 4K



**PTXX-SE-XX-G3:** Now with native NDI, this camera packs all the features of our three previous camera models (SDI-G2, USB-G2, & NDI-G2) into one. It provides more control options and video streaming options than the previous two cameras and at a better price.

The previous three models each targeted their own niche in the market.

**SDI-G2:** Hardwired live streaming, **NDI-G2:** Network based live streaming, and **USB-G2:** Conferencing. The **Move SE** is able to integrate seamlessly into all three and will replace these models.

### Move SE



# MODELS

## End of Life

## Current Gen

	SDI-G2	USB-G2	NDI-G2	Move-SE	LINK 4K	Move 4K
Video Format	1080p 60 fps	1080p 60 fps	1080p 60 fps	1080p 60 fps	4K 60 fps	4K 60 fps
Sensor	1/2.7" CMOS, Pixels: 2.07M	1/2.7" CMOS, Pixels: 2.07M	1/2.7" CMOS, Pixels: 2.07M	Sony 1/2.8 inch, CMOS, Pixels: 2.07M	<b>12X:</b> Sony 1/2.5 inch, CMOS, Pixels: 8.51M <b>20X &amp; 30X:</b> Sony 1/1.8 inch, CMOS, Pixels: 8.42M	<b>12X:</b> Sony 1/2.5 inch, CMOS, Pixels: 8.51M <b>20X &amp; 30X:</b> Sony 1/1.8 inch, CMOS, Pixels: 8.42M
Optical Zoom	12X, 20X, & 30X	12X, 20X	12X, 20X, & 30X	12X, 20X, & 30X	12X, 20X, & 30X	12X, 20X, & 30X
Digital Zoom	--	--	--	2X (960x540) 3X (640x360) 4X (480x270) 8X (240x135) 16X (128x72)	2X (1920x1080) 3X (1280x720) 4X (960x540) 8X (480x270) 16X (256x144)	2X (1920x1080) 3X (1280x720) 4X (960x540) 8X (480x270) 16X (256x144)
Color	Grey or White	Grey or White	Grey or White	Grey or White	Grey or White	Grey or White
Built-in Tally Light	--	--	--	--	YES	YES
Dante AV-H Native	--	--	--	--	YES	--
Control Options	IR RS-232 RS485 PELCO-D/P VISCA	IR RS-232 RS485 PELCO-D/P VISCA USB	IR, RS-232 RS485 PELCO-D/P VISCA NDI	IR, RS-232 RS485 PELCO-D/P VISCA NDI USB	IR, RS-232 RS485 PELCO-D/P VISCA Dante AV-H USB	IR, RS-232 RS485 PELCO-D/P VISCA NDI USB
Auto-Tracking	Not native. Basic auto-tracking through the CMP	Not native. Basic auto-tracking through the CMP	Not native. Basic auto-tracking through the CMP	Native & Web UI	Native & Web UI	Advanced Auto-Tracking Native & Web UI
Auto-Framing	--	--	--	--	--	Native & Web UI
LAN	H.264, H.265, & MJPEG RTMP/S	H.264, H.265, & MJPEG RTMP/S	H.264, H.265, & MJPEG RTMP/S	H.264, H.265, & MJPEG RTMP/S	H.264, H.265, MJPEG, YUY2, RTMP/S	H.264, H.265, & MJPEG RTMP/S
NDI	NDI upgradable	NDI upgradable	Native	Native	--	Native
Video Outputs	HDMI, 3G-SDI, CVBS NDI   HX Upgradable & IP	HDMI, USB 3.0, CVBS NDI   HX Upgradable & IP	NDI   HX, HDMI, 3G-SDI, IP, CVBS	HDMI 1.4, 3G-SDI, USB Type C 3.0, NDI   HX & IP	HDMI 2.0, 3G-SDI, USB Type A, Dante AV-H & IP	HDMI 2.0, 3G-SDI, USB Type A, NDI   HX & IP video
Streaming Protocols	TCP/IP, UDP, HTTP, RTSP, RTMP/RTMPS, ONVIF,	TCP/IP, UDP, HTTP, RTSP, RTMP/RTMPS, ONVIF,	TCP/IP, UDP, HTTP, RTSP, RTMP/RTMPS, ONVIF,	TCP/IP, UDP, HTTP, RTSP, RTMP/RTMPS, ONVIF, NDI, SRT, Multicast, etc.	TCP/IP, UDP, HTTP, RTSP, RTMP/RTMPS, ONVIF, SRT, Multicast, etc.	TCP/IP, UDP, HTTP, RTSP, RTMP/RTMPS, ONVIF, SRT, Multicast, etc.
Power	DC 12V / PoE (802.3af)	DC 12V / PoE (802.3af)	DC 12V / PoE (802.3af)	DC 12V / PoE (802.3af)	DC 12V / PoE+(802.3at)	DC 12V / PoE+(802.3at)
NDAA Compliant	--	--	--	YES	YES	YES
Warranty	5-year warranty	5-year warranty	5-year warranty	5-year warranty	5-year warranty	5-year warranty

### Copyright Notice

The entire contents of this manual / guide, whose copyright belongs to PTZOptics, may not be cloned, copied, or translated in any way without the explicit permission of the company. The product specifications referred to in this document are for reference only and as such are subject to updating at any time without prior notice.

484-593-2247

[ptzoptics.com/contact](http://ptzoptics.com/contact)

[ptzoptics.com](http://ptzoptics.com)



Covered by one or more claims of the HEVC patents listed at [patentlist.accessadvance.com](http://patentlist.accessadvance.com).