



DESCRIPTION

The R&M Cat. 6A coupler module is ideal for voice and data transmission at frequencies of up to 500 MHz. Simple connection of two patch cords via the coupler.

030.5955

TECHNICAL DATA

DESCRIPTION	VALUE/VALUE RANGE
Standard / norm	EN 50173-1 IEC 60603-7: Electrical Characteristics of the Telecommunication Outlets ISO/IEC 11801 ed. 2.2: June 2011 PL2 Class EA
Protection class IP	IP 20
PoE	Yes
PoE Level	4
Connector class	cable coupler
Shielding connector (A)	shielded
Connector type (A)	RJ45
Category connector (A)	Cat. 6 _A ISO
Poles	8

Coupler module,shielded, category 6A according to ISO/IEC 11801:2011, EN 50173-1:2011
EN 50173-1:2011 and EIA/TIA 568.2-D, RJ45 connection on both sides according to IEC 60603-7-1, >750 mating cycles.
EN 50173-1:2011 and EIA/TIA 568.2-D, meets class EA according to ISO/IEC 11801:2011
Material: Polycarbonat
Housing: Zinc alloy
Contact material: Spring Steel
Contact surface: Au / Ni

OPTIONAL ACCESSORY

FOTO	DESCRIPTION	PU	PRODUCT NO.
	Adapter C6 EL, 6A /u Keystone 3rd Gen.	10 pcs	R837033
	Adapter C6 EL, 6A /s Keystone 3rd Gen.	10 pcs	R837034
	Adapter C6 EL, C6A /u Keystone LARGE 20.3mm	10 pcs	R848274
	Adapter Freenet for EL/ISO modules /u-24	24 pcs	R513484
	Adapter Freenet for EL/ISO modules /s-24	24 pcs	R513483
	Adapter No.1 EL /u 10x	10 pcs	R832197

FOTO	DESCRIPTION	PU	PRODUCT NO.
------	-------------	----	-------------



RCB Connecting Box IP20

1 pcs

R316999