

Cables / Connectors / Leads / Stage Boxes




Part No: RW240624BK

	(14/0.12BC x 2C + PE Insulation + Drain Wire + 26/0.12BC Left Spiral	
Description	Shield + 26/0.12BC Right Spiral Shield + Inner Sheath) x 6C + Cotton Wire + Cotton Paper + Outer Sheath 11.7mm	
Applicable Standards	N/A	
Suitable Applications	Used to connect multiple audio channels in low level (microphone) and high level (line) componentry such as console board equipment for Radio television stations, post-production facilities, and sound system installation where superior flexibility is required.	

Cable Construction Drawing

Cable Construction Relative Parts





Cable Description

Conductor	14/0.12+/-0.006BC		
Insulation	Pair: 6 Material: PE Colour: Red/Black Min. Thickness 0.20mm / Nom. Thickness 0.25mm / Nom. O.D 1.03+/-0.1mm		
Drain Wire	19/0.12+/-0.006TC		
Chielding	26/0.12+/-0.006mmBC Left Spiral Shield		
Shielding	26/0.12+/-0.006mmBC Right Spiral Shield		
	Material: PVC / Colour: Brown, Red, Orange, Yellow, Green, Blue		
Inner Sheath	Min. Thickness 0.30mm / Nom. Thickness 0.35mm / Nom. Sheath O.D 3.3+/-0.1mm		
onoutri	Spark Voltage: 3000V a.c		
Filler	Material: Cotton Wire, Cotton Paper		
	Material: PVC / Colour: Black		
Outer Sheath	Min. Thickness 0.64mm / Nom. Thickness 0.80mm / Nom. Sheath O.D11.7+/-0.2mm		
Chouth	Spark Voltage: 3000V a.c		





Cables / Connectors / Leads / Stage Boxes



Electrical Properties

Conductor Max D.C Resistance	117.77 ohm/km 20°C
Voltage Test: Core to Core	1000V a.c/1min
Voltage Test: Core to Screen	1000V a.c/1min

Physical Properties

Insulation Elongation	300%
Insulation Tensile Strength	13.6 N/mm ²
Inner Sheath Elongation	100%
Inner Sheath Tensile Strength	12 N/mm ²
Sheath Elongation	100%
Sheath Tensile Strength	12 N/mm ²

Mechanical Properties

Operating Temperature Range	-15 to 70°C		
Max. Recommended Pulling Tension	156N		
Min. Bend Radius (install)	117mm		
Approximate Mass	17.66kg/100m		
Shooth Drinting	ROADWORX RW240624 Analog Audio Snake, 6 pair,		
Sheath Printing	flexible, 24AWG (meter marking)		

Supply Information

Pack Size	Pack Type	Dimensions		Qty Per Pack		Qty Per Pallet	
500m	Wooden Reel	W60 x H51cm		1R		_	
Document Change Record		Issue	Date	e	Prepared	by Approved By	
		Sales	28-0	-03-2013 LLS		Pent	
		Issue		Change			
Change History							

