

Audio Visual Technologies

Cables / Connectors / Leads / Stage Boxes

## Part No: RW241624BK


Description	(14/0.12BC x 2C + PE Insulation + Drain Wire + 26/0.12BC Left Spiral Shield + 26/0.12BC Right Spiral Shield + Inner Sheath) x 16C + Cotton Paper + Outer Sheath 17.5mm
Applicable Standards	N/A
Suitable Applications	Used to connect multiple audio channels in low level (microphone) and high level (line) componentry such as console board equipment for Radio television stations, post-production facilities, and sound

system installation where superior flexibility is required.

Cable Construction Drawing

Cable Construction Relative Parts





Cable De	scription				
Conductor	14/0.12+/-0.006BC				
Insulation	Pair: 16 Material: PE Colour: Red/Black Min. Thickness 0.20mm / Nom. Thickness 0.25mm / Nom. O.D 1.03+/-0.1mm				
Drain Wire	19/0.12+/-0.006TC				
Shielding	26/0.12+/-0.006mmBC Left Spiral Shield				
	26/0.12+/-0.006mmBC Right Spiral Shield				
Inner Sheath	Core: 16 Material: PVC				
	Min. Thickness 0.30mm / Nom. Thickness 0.35mm / Nom. Sheath 0.D 3.3+/-0.1mm				
	Spark Voltage: 3000V a.c				
Filler	Material: Cotton Paper				
Outer Sheath	Material: PVC / Colour: Black				
	Min. Thickness 0.64mm / Nom. Thickness 0.80mm / Nom. Sheath 0.D17.5+/-0.2mm				
	Spark Voltage: 3000V a.c				





Cables / Connectors / Leads / Stage Boxes

Electrical Properties					
Conductor Max D.C Resistance		117.77 ohm/km 20°C			
Voltage Test: Core to Core		1000V a.c/1min			
Voltage Test: Core to Screen	10	1000V a.c/1min			
Physical Properties					
Insulation Elongation	,	300%			
Insulation Tensile Strength		13.6 N/mm <sup>2</sup>			
Inner Sheath Elongation		100%			
Inner Sheath Tensile Strength		12 N/mm <sup>2</sup>			
Sheath Elongation		100%			
Sheath Tensile Strength		12 N/mm <sup>2</sup>			
Mechanical Properties					
Operating Temperature Range		-15 to 70°C			
Max. Recommended Pulling Tension		681N			
Min. Bend Radius (install)		175mm			
Approximate Mass		42.1kg/100m			
Sheath Printing		ROADWORX RW241624 Analog Audio Snake, 16 pair, flexible, 24AWG (meter marking)			
	110	Mibie, 24AWG (Mete	i iliai kirig)		
Supply Information					
Pack Size Pack Type	I	Dimensions	Qty Per Pack	Qty Per Pallet	
300m Wooden Reel	W	/65 x H51cm	1R		
Decument Change Decard	Issue	Date	Prepared by	Approved By	
Document Change Record	Sales	28-03-2013	LLS	Pent	

